

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/324279275>

# Modeling of bending–torsion couplings in active–bending structures. Application to the design of elastic gridshells.

Thesis · December 2017

CITATIONS

12

READS

249

1 author:



Lionel du Peloux

École des Ponts ParisTech

20 PUBLICATIONS 194 CITATIONS

SEE PROFILE

Some of the authors of this publication are also working on these related projects:



thinkshell.fr [View project](#)



active bending [View project](#)



# ELASTIC **GRIDSHELL**

Lionel du Peloux

---



*Modeling of bending-torsion couplings  
in active-bending structures*

application to

# **THE DESIGN OF ELASTIC GRIDSHELLS**

Lionel du Peloux de Saint Romain  
PhD Thesis 2017



# THESE DE DOCTORAT

*Modeling of bending-torsion couplings in active-bending structures. Application to the design of elastic gridshells.*

Université Paris-Est  
Laboratoire UMR Navier  
Ecole Doctorale Science, Ingénierie et Environnement  
Spécialité Structures et Matériaux

Auteur Lionel **DU PELOUX DE SAINT ROMAIN**  
Lieu Ecole Nationale des Ponts et Chaussées  
Date 20 décembre 2017

Président Bernard **MAURIN**  
Rapporteurs Sébastien **NEUKIRSH**  
Carlos **LÁZARO**  
Examineurs Alberto **PUGNALE**  
Jean-François **CARON**  
Cyril **DOUTHE**  
Invité Bernard **VAUDEVILLE**  
Directeur Olivier **BAVEREL**



*“Quia nominor leo.”*

À Jacques & Christiane,  
Mes grands-parents bien-aimés.







# ABSTRACT

An *elastic gridshell* is a freeform structure, generally doubly curved, but formed out through the reversible deformation of a regular and initially flat structural grid. Building curved shapes that may seem to offer the best of both worlds : shell structures are amongst the most performant mechanically speaking while planar and orthogonal constructions are much more efficient and economic to produce than curved ones. This ability to “form a form” efficiently is of peculiar importance in the current context where morphology is a predominant component of modern architecture, and envelopes appear to be the neuralgic point for building performances.

The concept was invented by Frei Otto, a German architect and structural engineer who devoted many years of research to gridshells. In 1975 he designed the Multihalle of Mannheim, a 7500 m<sup>2</sup> wooden shell which demonstrated the feasibility of this technology and made it famous to a wide audience. However, despite their potential, very few projects of this kind were built after this major realization. And for good reason, the resources committed at that time cannot guarantee the replicability of this experiment

for more standard projects, especially on the economic level. Moreover, the technics and methods developed by Otto's team in the 1960s have mostly fall into disuse or are based on disciplines that have considerably evolved. New materials, such as composite materials, have recently emerged. They go beyond the limitations of conventional materials such as timber and offer at all levels much better technical performances for this kind of application. Finally, it should be noted that the regulatory framework has also deeply changed, bringing a certain rigidity to the penetration of innovations in the building industry. Therefore, the design of gridshells arises in new terms for current architects and engineers and comes up against the inadequacy of existing tools and methods.

In this thesis, which marks an important step in a personal research adventure initiated in 2010, we try to embrace the issue of the design of elastic gridshells in all its complexity, addressing both theoretical, technical and constructive aspects. In a first part, we deliver a thorough review of this topic and we present in detail one of our main achievements, the ephemeral cathedral of Créteil, built in 2013 and still in service. In a second part, we develop an original discrete beam element with a minimal number of degrees of freedom adapted to the modeling of bending and torsion inside gridshell members with anisotropic cross-section. Enriched with a ghost node, it allows to model more accurately physical phenomena that occur at connections or at supports. Its numerical implementation is presented and validated through several test cases. Although this element has been developed specifically for the study of elastic gridshells, it can advantageously be used in any type of problem where the need for an interactive computation with elastic rods taking into account flexion-torsion couplings is required.

**Keywords :** gridshell, form-finding, active-bending, free-form, torsion, elastic rod, coupling, fibreglass, composite material.

# RÉSUMÉ

Les structures de type *gridshell élastique* permettent de réaliser des enveloppes courbes par la déformation réversible d'une grille structurelle régulière initialement plane. Cette capacité à "former la forme" de façon efficiente prend tout son sens dans le contexte actuel où, d'une part la forme s'impose comme une composante prédominante de l'architecture moderne, et d'autre part l'enveloppe s'affirme comme le lieu névralgique de la performance des bâtiments.

Fruit des recherches de l'architecte et ingénieur allemand Frei Otto dans les années 1960, elles ont été rendues populaires par la construction de la Multihalle de Mannheim en 1975. Cependant, en dépit de leur potentiel, très peu de projets de ce type ont vu le jour suite à cette réalisation emblématique qui en a pourtant démontré la faisabilité à grande échelle. Et pour cause, les moyens engagés à l'époque ne sauraient assurer la reproductibilité de cette expérience dans un contexte plus classique de projet, notamment sur le plan économique. Par ailleurs, les techniques et les méthodes développées alors sont pour la plus part tombées en désuétude ou reposent sur des disciplines scientifiques qui ont considéra-

blement évoluées. Des matériaux nouveaux, composites, ont vu le jour. Ils repoussent les limitations intrinsèques des matériaux usuels tel que le bois et offrent des performances techniques bien plus intéressantes pour ce type d'application. Enfin, notons que le cadre réglementaire a lui aussi profondément muté, apportant une certaine rigidité vis-à-vis de la pénétration des innovations. Ainsi la conception des gridshells se pose-t-elle en des termes nouveaux aux architectes et ingénieurs actuels et se heurte à l'inadéquation des outils et méthodes existant.

Dans cette thèse, qui marque une étape importante dans une aventure de recherche personnelle initiée en 2010, nous tentons d'embrasser la question de la conception des gridshells élastiques dans toute sa complexité, en abordant aussi bien les aspects théoriques que techniques et constructifs. Dans une première partie, nous livrons une revue approfondie de cette thématique et nous présentons de façon détaillée l'une de nos principales réalisations, la cathédrale éphémère de Créteil, construite en 2013 et toujours en service. Dans une seconde partie, nous développons un élément de poutre discret original avec un nombre minimal de degrés de liberté adapté à la modélisation de la flexion et de la torsion dans les gridshells constitués de poutres de section anisotrope. Enrichi d'un noeud fantôme, il permet de modéliser plus finement les phénomènes physiques au niveau des connexions et des appuis. Son implémentation numérique est présentée et validée sur quelques cas tests. Bien que cet élément ait été développé spécifiquement pour l'étude des gridshells élastiques, il pourra avantageusement être utilisé dans tout type de problème où la nécessité d'un calcul interactif avec des tiges élastiques prenant en compte les couplages flexion-torsion s'avère nécessaire.

**Keywords** : gridshell, form-finding, active-bending, free-form, torsion, elastic rod, coupling, fibreglass, composite material.



# CONTENTS

Préface	<b>xi</b>
Abstract (English/Français)	<b>xv</b>
Contents	<b>xix</b>
List of Figures	<b>xxix</b>
List of Tables	<b>xxxvii</b>

■ ■ ■

# Introduction 1

■ Part I : Elastic gridshells ■

## 1 Elastic gridshells 9

### 1.1 Introduction 9

Overview 9

Contributions 10

### 1.2 Definition 10

Erection process 10

Structural typology 12

Material flexibility for structural rigidity 12

### 1.3 Built elastic gridshells : a review 12

The beginnings : from the first prototype to the German Pavilion 14

Mannheim Multihalle : the completion of a decade of research 18

The dry period : 25 years from Mannheim to Hannover 22

The signs of a renewal : Dorset and Doncaster 22

The renewal : Hannover, Downland and Savill 24

Gridshell in composite materials : a new perspective 34

Flourishing timber gridshell pavilions 38

Latest experiments 43

### 1.4 Research works on elastic gridshells : a review 44

Mechanics 44

Geometry 46

Material 47

Technology 47

### 1.5 Conclusion 48

## 2 Ephemeral cathedral 55

### 2.1 Introduction 55

Overview 56

Contributions	56
<b>2.2 Project overview</b>	<b>57</b>
Context and challenges	57
Architectural considerations on the form	59
Placing of the building on the site	59
Entrance	60
Daylight	60
Technical description	64
<b>2.3 Construction process</b>	<b>70</b>
Assembly of the grid	70
Deformation of the grid	70
Bracing of the grid	70
Covering of the gridshell	73
<b>2.4 Structural design</b>	<b>73</b>
Overall design process	73
3D modelling of the intended shape	74
Meshing the surface	75
Form-finding and bending prestress	78
As-built geometry	80
Structural analysis	81
<b>2.5 Designing with GFRP materials</b>	<b>81</b>
Properties of the tubes	81
Codes for composite materials	83
Flexural strength of the tubes	84
Partial safety factors	84
<b>2.6 Construction details</b>	<b>86</b>
The swivel coupler	86
The sleeve system	92
Foundations	98
The membrane	98
<b>2.7 Hygrothermal behavior</b>	<b>101</b>
Temperature	101
Moisture	104
<b>2.8 Cost analysis</b>	<b>104</b>
Overall cost for the client	104
Cost details for the building	107
Strengths and weaknesses	114

<b>2.9 Conclusions</b>	<b>115</b>
------------------------	------------

■ Part II : Kirchhoff beam model ■

## **3 Geometry of discrete curves** **123**

<b>3.1 Introduction</b>	<b>123</b>
Overview	124
Contributions	125
Related work	125
<b>3.2 Parametric curves</b>	<b>126</b>
Definition	127
Regularity	127
Reparametrization	127
Natural parametrization	128
Curve length	128
Arc length parametrization	128
<b>3.3 Frenet trihedron</b>	<b>129</b>
Tangent vector	129
Normal vector	130
Binormal vector	131
Osculating plane	132
<b>3.4 Curves of double curvature</b>	<b>132</b>
First invariant : the curvature	133
Second invariant : the torsion	136
Fundamental theorem of space curves	137
Serret-Frenet formulas	137
<b>3.5 Curve framing</b>	<b>139</b>
Moving frame	139
Adapted moving frame	143
Rotation-minimizing frame	144
Parallel transport	144
Frenet frame	145
Bishop frame	147
Comparison between Frenet and Bishop frames	149

<b>3.6 Discrete curves</b>	<b>152</b>
Definition	153
Regularity	154
Parametrization	155
<b>3.7 Discrete curvature</b>	<b>156</b>
Definition from osculating circles	156
Benchmarking : sensitivity to non uniform discretization	161
Benchmarking : accuracy in bending energy representation	164
<b>3.8 Discrete tangent vector</b>	<b>170</b>
Circumscribed case	170
Inscribed case	173
<b>3.9 Discrete parallel transport</b>	<b>176</b>
The rotation method	177
The double reflexion method	177
<b>3.10 Conclusion</b>	<b>179</b>
<b>4 Elastic rod : variational approach</b>	<b>183</b>
<b>4.1 Introduction</b>	<b>183</b>
Overview	184
Contributions	184
Related work	185
<b>4.2 Kirchhoff rod</b>	<b>186</b>
Description of the motion	186
Inextensibility assumption	187
Euler-Bernoulli assumption	188
Motion of the material frame	188
Material curvatures and twist	189
Material constitutive equations	190
Elastic energy	190
<b>4.3 Curve-angle representation</b>	<b>191</b>
Definition of the representation	192
Measurement of the material twist	193
Vector of material curvatures	194

<b>4.4</b>	<b>Definition of the variational problem</b>	<b>194</b>
	Calculus of variations	194
	Prerequisite for the computation of energy gradients	196
	Coupling between bending and torsion	196
	Quasistatic assumption	196
<b>4.5</b>	<b>Energy gradient with respect to <math>\theta</math> : twisting moment</b>	<b>197</b>
	Derivative of material directors with respect to $\theta$	197
	Derivative of the material curvatures vector with respect to $\theta$	197
	Computation of the twisting moment	198
<b>4.6</b>	<b>Energy gradient with respect to <math>\mathbf{x}</math> : internal forces</b>	<b>200</b>
	Derivative of material directors with respect to $\mathbf{x}$	200
	Derivative of the vector of material curvatures with respect to $\mathbf{x}$	208
	Computation of the forces acting on the centerline	209
<b>4.7</b>	<b>Shear force acting on the rod</b>	<b>213</b>
<b>4.8</b>	<b>Discussion</b>	<b>213</b>
<b>4.9</b>	<b>Conclusion</b>	<b>214</b>

## **5 Elastic rod : equilibrium approach** **219**

<b>5.1</b>	<b>Introduction</b>	<b>219</b>
	Overview	220
	Contributions	221
	Related work	221
<b>5.2</b>	<b>Introduction to the special Cosserat theory of rods</b>	<b>222</b>
	Description of the motion	223
	Time evolution	229
	Force and moment strains	230
	Parametrization of the centerline	231
	To go further	232
<b>5.3</b>	<b>Kirchhoff theory of rods</b>	<b>232</b>
	Description of the motion	233
	Reparametrization	236
	Force and moment strains	237
	Balance of momentum	239
	Equations of motion	246
	Hookean elasticity	247

Deformation of cross-sections	248
Strain tensor	250
Stress tensor	250
Constitutive equations for internal forces and moments	250
Discussion	252
<b>5.4 Summary of Kirchhoff theory</b>	<b>253</b>
<b>5.5 Geometric interpretation of Kirchhoff's equations</b>	<b>256</b>
influence of the curvature ( $\kappa$ )	259
influence of the first material curvature ( $\kappa_1$ )	261
Influence of the second material curvature ( $\kappa_2$ )	265
<b>5.6 Conclusion</b>	<b>267</b>
<b>6 Numerical Model</b>	<b>271</b>
<b>6.1 Introduction</b>	<b>271</b>
Overview	272
Contributions	273
Related works	273
<b>6.2 Discrete beam element</b>	<b>275</b>
Description of the element	277
Modeling of discontinuities	279
Matrix notation	280
Discrete extension and axial force	281
Discrete curvature and bending moment	281
Discrete rate of twist and twisting moment	285
Discrete shear force	286
Interpolation of the internal forces and moments	288
<b>6.3 Dynamic Relaxation</b>	<b>290</b>
Overview of the procedure	291
Resultants acting on a particle	291
Equations of motion	293
Explicit time integration	294
Damping	297
Convergence	300
Stability and critical damping	302
Application to the simple plane pendulum	304

<b>6.4</b>	<b>Enriching the model</b>	<b>309</b>
	Support condition	309
	Connection	310
<b>6.5</b>	<b>Software</b>	<b>311</b>
	Architecture of the software	311
	Structure of the algorithm	312
	Key aspects	312
	Performance	315
<b>6.6</b>	<b>Test case</b>	<b>317</b>
	Constrained arch	317
<b>6.7</b>	<b>Conclusion</b>	<b>323</b>

## **Conclusion** **327**

■ Part III : Appendix ■

## **A** Review of built elastic gridshells **337**

## **B** Calculus of variations **341**

<b>B.1</b>	<b>Introduction</b>	<b>341</b>
<b>B.2</b>	<b>Spaces</b>	<b>341</b>
	Normed space	341
	Inner product space	342
	Euclidean space	342
	Banach space	342
	Hilbert space	343
<b>B.3</b>	<b>Derivative</b>	<b>343</b>
	Fréchet derivative	343
	Gâteaux derivative	344
	Useful properties	346
	Partial derivative	346

B.4	Gradient vector	347
B.5	Jacobian matrix	347
B.6	Hessian	348
B.7	Functional	348

## C Parabolic interpolation 351

C.1	Introduction	351
C.2	Lagrange interpolating polynomial	352
C.3	Reparametrization	352
C.4	Characteristic values	353
C.5	Extremum value	354

■ ■ ■

Index of notation	355
Bibliography	359
Publications from the author	371



# LIST OF FIGURES

1.1	Forming process of the gridshell of Mannheim, Germany	11
a	Assembly of the timber grid	11
b	Deformation of the grid	11
c	Final shape of the lattice	11
d	Roofing with a membrane	11
1.2	Known elastic gridshells built by the past	13
1.3	Steel gridshell built in 1962 in Berkeley, USA	15
a	Steel lattice	15
b	Knot detail	15
1.4	Timber gridshell built in 1962 in Essen, Germany	15
1.5	Timber gridshell built in 1967 in Montreal, Canada	16
1.6	Timber gridshell built in 1975 in Mannheim, Germany	19
a	Sky view	19
b	Interior view	20

## LIST OF FIGURES

---

<b>1.7</b>	<b>Roundwood gridshell built in 1995 in Dorset, England</b>	<b>23</b>
a	Interior view	23
b	Exterior view	23
<b>1.8</b>	<b>Timber gridshells built in 1998 in Doncaster, England</b>	<b>23</b>
a	Interior view	23
b	Exterior view	23
<b>1.9</b>	<b>Cardboard gridshell built in 2000 in Hannover, Germany</b>	<b>25</b>
a	Sky view	25
b	Interior view	25
c	Knot detail	25
<b>1.10</b>	<b>Timber gridshell built in 2002 in Downland, England</b>	<b>27</b>
a	Interior view	27
b	Exterior view	27
<b>1.11</b>	<b>Construction stages of the Downland gridshell</b>	<b>28</b>
a	Flat grid on scaffold platform	28
b	Deformed grid	28
c	Triangulated grid	29
d	Final structure with cladding	29
<b>1.12</b>	<b>Timber gridshell built in 2002 in Pishwanton, England</b>	<b>31</b>
a	Interior view	31
b	Exterior view	31
<b>1.13</b>	<b>Timber gridshells built in 1998 in Doncaster, England</b>	<b>31</b>
a	Interior view	31
b	Exterior view	31
<b>1.14</b>	<b>Timber gridshell built in 2006 in Savill, England</b>	<b>32</b>
a	Interior view	32
b	Exterior view	32
<b>1.15</b>	<b>Timber gridshell built in 2007 in Kent, England.</b>	<b>32</b>
a	Glazing support	32
b	Exterior view	32
<b>1.16</b>	<b>GFRP gridshells built in 2006 and 2007 in Noisy-Champs, France</b>	<b>35</b>
a	First prototype 2006	35
b	Second prototype 2007	35
<b>1.17</b>	<b>Solidays GFRP gridshell built in 2011 in Paris, France</b>	<b>36</b>
<b>1.18</b>	<b>GFRP gridshell built in 2013 in Créteil, France</b>	<b>37</b>
a	Interior view	37

b Exterior view	37
<b>1.19 Timber gridshells built by gridshell.it in Italy</b>	<b>39</b>
a Lecce 2010	39
b Toledo 2014	39
<b>1.20 Timber gridshell built in 2013 in San Antonio, USA</b>	<b>39</b>
a Folding skin	39
b Pavilion	39
<b>1.21 Timber gridshell built in 2016 in Montpellier, France</b>	<b>41</b>
a Pavilion	41
b Tensioner	41
<b>1.22 Timber gridshell built in 2016 in Champs-sur-Marne, France</b>	<b>42</b>
a Robotic manufacturing	42
b Timber lattice	42
<b>1.23 Hybrid structural skin built in 2016 in Champs-sur-Marne, France</b>	<b>42</b>
a Interior view	42
b Concrete shell	42
■ ■ ■	
<b>2.1 Situation map</b>	<b>58</b>
<b>2.2 Architectural sketch</b>	<b>58</b>
<b>2.3 Steel doors</b>	<b>60</b>
a Interior view	60
b Exterior view	60
<b>2.4 Exterior view of the gridshell</b>	<b>61</b>
<b>2.5 Interior view of the gridshell</b>	<b>62</b>
<b>2.6 Key elements of the structural system</b>	<b>65</b>
a Swivel coupler	65
b Sleeve system	65
c Ground anchorage	65
d Lacing rod	65
<b>2.7 Top view of the building</b>	<b>67</b>
<b>2.8 Transversal section of the building</b>	<b>68</b>
<b>2.9 Assembly of the grid</b>	<b>71</b>
a GFRP tubes with swivel couplers	71

## LIST OF FIGURES

---

b Primary grid	71
c Cranes ready to lift the grid	71
<b>2.10 Deformation of the grid</b>	<b>71</b>
a Beginning of the deformation	71
b Grid largely deformed	71
c Fixing the grid	71
<b>2.11 Bracing of the grid</b>	<b>72</b>
a Before triangulation	72
b After triangulation	72
<b>2.12 Installation of the membrane</b>	<b>72</b>
a Unpacking the membrane	72
b Pulling the membrane in the grid	72
c The membrane is in place	72
<b>2.13 Benchmarking shapes regarding their curvature</b>	<b>75</b>
<b>2.14 The compass method step by step</b>	<b>77</b>
a Target shape	77
b Domain and trimming surfaces	77
c Secant directrices	77
d Resulting mesh	77
e Trimmed mesh	77
f Final grid	77
<b>2.15 Principle of the compass method</b>	<b>77</b>
<b>2.16 Permanent bending stresses in the structure under self-weight</b>	<b>79</b>
<b>2.17 Reconstruction of the full 3D geometry</b>	<b>80</b>
a Wire frame	80
b Full 3D	80
<b>2.18 Flexural test of the GFRP tubes</b>	<b>85</b>
<b>2.19 Technical drawing of the swivel coupler</b>	<b>87</b>
<b>2.20 Influence of the interface layer on the sliding resistance</b>	<b>88</b>
<b>2.21 Influence of the tightening on the sliding resistance</b>	<b>89</b>
<b>2.22 Influence of the temperature on the sliding resistance</b>	<b>90</b>
<b>2.23 Technical drawing of the sleeve system</b>	<b>92</b>
<b>2.24 Design and behavior of the the sleeve system</b>	<b>93</b>
a Solidays 2011	93
b Créteil 2013	93
c Continuity of curvature	93

d	Plastification threshold	93
<b>2.25</b>	<b>Typical failure modes when testing the sleeve system in traction</b>	<b>95</b>
a	Tearing	95
b	Contact compression	95
<b>2.26</b>	<b>Typical failure modes of a bolt in a pultruded element</b>	<b>96</b>
a	Geometry	96
b	Fibres	96
c	Cleavage	96
d	Tearing	96
e	Inclined compression	96
f	Contact compression	96
<b>2.27</b>	<b>Tensile test of the pinned connection</b>	<b>97</b>
<b>2.28</b>	<b>Technical drawing of the footing</b>	<b>99</b>
<b>2.29</b>	<b>Weather data at site location during opening hours</b>	<b>102</b>
a	Temperature	102
b	Solar radiation	102
<b>2.30</b>	<b>Temperature inside the building during opening hours</b>	<b>103</b>
a	Without ventilation	103
b	With ventilation	103
<b>2.31</b>	<b>Cost allocation for the whole project</b>	<b>105</b>
<b>2.32</b>	<b>Cost allocation per square meter of covered area</b>	<b>106</b>
<b>2.33</b>	<b>Allocation of the man-hours spent by the volunteers</b>	<b>109</b>
<b>2.34</b>	<b>Cost allocation for masonry works</b>	<b>111</b>
<b>2.35</b>	<b>Cost allocation for the superstructure</b>	<b>113</b>



<b>3.1</b>	<b>Definition of the tangent vector and the osculating circle of a curve</b>	<b>131</b>
a	Curve's tangent	131
b	Curve's normal and osculating circle	131
<b>3.2</b>	<b>Osculating circles for a spiral curve at different parameters</b>	<b>135</b>
<b>3.3</b>	<b>Discontinuity of the Frenet trihedron at an inflexion point</b>	<b>137</b>
<b>3.4</b>	<b>Geometric interpretation of the angular velocity vector of a moving frame</b>	<b>141</b>
<b>3.5</b>	<b>Adapted moving frame on a circular helix</b>	<b>141</b>

## LIST OF FIGURES

---

<b>3.6</b>	<b>Angular velocities of Frenet and Bishop frames for a circular helix</b>	<b>150</b>
a	Frenet frame	150
b	Bishop Frame	151
<b>3.7</b>	<b>Discrete curve representation and parametrization</b>	<b>153</b>
<b>3.8</b>	<b>Several ways to define the osculating circle for discrete curves</b>	<b>157</b>
a	Vertex-based	157
b	Edge-based	157
c	Bitangent with $\ \mathbf{e}_{i-1}\ $	157
d	Bitangent with $\ \mathbf{e}_i\ $	157
<b>3.9</b>	<b>Sensitivity of discrete curvatures to non uniform discretization</b>	<b>162</b>
a	Circumscribed ( $\varphi = \pi/3$ )	162
b	Circumscribed ( $\varphi = 2\pi/3$ )	162
c	Inscribed ( $\varphi = \pi/3$ )	162
d	Inscribed ( $\varphi = 2\pi/3$ )	162
<b>3.10</b>	<b>Sensitivity of discrete curvatures to non uniform discretization</b>	<b>163</b>
<b>3.11</b>	<b>Discretization of a semicircle and evaluation of its bending energy</b>	<b>166</b>
<b>3.12</b>	<b>Relative error in the estimation of the bending energy of a semicircle</b>	<b>167</b>
a	$ 1 - \frac{\varepsilon_1}{\varepsilon}(n) $ in %	167
b	$ 1 - \frac{\varepsilon_3}{\varepsilon}(n) $ in %	167
<b>3.13</b>	<b>Discretization of an elastica curve and evaluation of its bending energy</b>	<b>168</b>
a	Sequence of elastica curves	168
b	Zoom on the discretization	168
<b>3.14</b>	<b>Relative error in the estimation of the bending energy of an elastica</b>	<b>169</b>
a	$ 1 - \frac{\varepsilon_1}{\varepsilon}(n) $ in %	169
b	$ 1 - \frac{\varepsilon_3}{\varepsilon}(n) $ in %	169
<b>3.15</b>	<b>Definition of the tangent vector associated to the circumscribed curvature</b>	<b>171</b>
a	Current portion	171
b	Start	171
c	End	171
<b>3.16</b>	<b>Definition of the tangent vector associated to the inscribed curvature</b>	<b>174</b>
a	Current portion	174
b	Start	174
c	End	174
<b>3.17</b>	<b>Two methods to parallel transport a vector</b>	<b>178</b>
a	Rotation method	178

b Double reflection method	178
----------------------------	-----

■ ■ ■

<b>4.1 Curve-angle representation of the rod</b>	192
a Bending strains	192
b Angular deviation	192
<b>4.2 Succession of the degrees of freedom</b>	195
<b>4.3 Variation of the Bishop frame for a perturbation of the centerline</b>	201
<b>4.4 Measuring the variation of parallel transport : rotation of angle <math>\alpha_\epsilon</math>.</b>	202
<b>4.5 Measuring the variation of parallel transport : rotation of angle <math>\Psi_\epsilon</math>.</b>	203

■ ■ ■

<b>5.1 Description of the motion for a Cosserat rod : longitudinal section</b>	224
<b>5.2 Description of the motion for a Cosserat rod : transverse section</b>	225
a Deformed cross-section $\mathcal{S}(s)$	225
b Deformed cross-section $\mathcal{S}(s + ds)$	225
c Reference cross-section $\bar{\mathcal{S}}(s)$	225
d Reference cross-section $\bar{\mathcal{S}}(s + ds)$	225
<b>5.3 Equilibrium of an infinitesimal slice of rod</b>	241
<b>5.4 Typical deformation modes of cross-sections in Kirchhoff's theory</b>	249
<b>5.5 Geometric interpretation of Kirchhoff's equations</b>	257
<b>5.6 Geometric interpretation : influence of the curvature (<math>\kappa</math>)</b>	258
a Infinitesimal deformation	258
b Contributions of the internal forces	258
c Contributions of the internal moments	258
<b>5.7 Geometric interpretation : influence of the first material curvature (<math>\kappa_1</math>)</b>	260
a Infinitesimal deformation	260
b Contributions of the internal forces	260
c Contributions of the internal moments	260
<b>5.8 Geometric interpretation : influence of the second material curvature (<math>\kappa_2</math>)</b>	264
a Infinitesimal deformation	264
b Contributions of the internal forces	264

## LIST OF FIGURES

---

c Contributions of the internal moments	264
■ ■ ■	
6.1 Centerline of the discrete biarc model	276
6.2 Calculation of the biarc parameters	283
a Geometric curvature at ghost vertices	283
b Unit tangent vector at ghost vertices	283
c Left/right unit tangent vector at handle vertices	283
d Unit tangent vector at handle vertices	283
e Left/right bending moment at handle vertices	283
6.3 Parabolic interpolation of the kinetic energy peak	299
6.4 Application of the DR process to the simple plane pendulum	306
a First steps until the first peak of $\mathcal{E}_k$ is reached	306
b Potential energy of the pendulum for the first steps	306
6.5 Convergence of the DR process for the simple plane pendulum	307
a Typical profile of the kinetic damping	307
b Convergence of the DR process in the phase space	307
6.6 Partial class diagram of <i>Marsupilami.Math.dll</i>	313
6.7 Test case of a constrained arch	318
6.8 Comparison of normalized force diagrams	319



# LIST OF TABLES

2.1	Key figures	66
2.2	Technical properties of the tube	82
2.3	Flexural tests of the GFRP tubes	84
2.4	Short-term and long-term values for material resistance	84
2.5	Technical properties of the membrane	100
2.6	Man-hours spent by the volunteers on the fabrication	108
2.7	Cost details for masonry works	110

LIST OF TABLES

---

2.8	Cost details for the superstructure	112
	■ ■ ■	
3.1	Review of several discrete curvature definitions	158
	■ ■ ■	
5.1	Summary of the notations employed throughout this section	226
	■ ■ ■	
6.1	Number of segments, edges and vertices whether the centerline is closed or open	276
6.2	Simple cost model for arithmetic operations	316
6.3	Internal forces for the arch test case	320
6.4	Internal moments for the arch test case	321
6.5	Geometric parameters for the arch test case	322
	■ ■ ■	
A.1	Project review - general informations	338
A.2	Project review - key numbers	339

# INTRODUCTION

La paternité des structures de type *gridshell élastique* est couramment attribuée à l'architecte et ingénieur allemand Frei Otto, qui les a intensivement étudiées au XX<sup>ème</sup> siècle. Fruit de son travail de recherche, il réalise en 1975, en collaboration avec l'ingénieur Edmund Happold du bureau Arup, un projet expérimental de grande ampleur : la Multihalle de Mannheim [1, 2]. Cette réalisation emblématique ancrera durablement les gridshells dans le paysage des typologies structurelles candidates à l'avènement de géométries non-standard, caractérisées par l'absence d'orthogonalité. Cette capacité à *former la forme* de façon efficiente prend tout son sens dans le contexte actuel où, d'une part la forme s'impose comme une composante prédominante de l'architecture moderne (F. Gehry, Z. Hadid, ...) et d'autre part l'enveloppe s'affirme comme le lieu névralgique de la performance des bâtiments, notamment environnementale.

Littéralement, le terme *grid-shell* désigne une résille à double courbure dont le comportement mécanique s'apparente à celui d'une coque ; c'est à dire que les efforts y transitent principalement de manière membranaire. Ces ouvrages peuvent franchir de grandes por-

tées en utilisant un minimum de matière. Cependant, il semble plus rigoureux et plus fidèle à l'histoire de désigner par *gridshell élastique* la combinaison indissociable d'un principe structurel – le gridshell, une résille qui fonctionne telle une coque – et d'une méthode constructive astucieuse – la déformation réversible d'une grille de poutre initialement plane pour former une surface tridimensionnelle à double courbure. Le projet de Mannheim – dans lequel une grille en bois de trame régulière, initialement plane et sans rigidité de cisaillement est déformée élastiquement jusqu'à la forme désirée via un dispositif d'étalement, puis contreventée pour mobiliser la raideur d'une coque et finalement couverte d'une toile – pose les bases de ce nouveau concept et le rend populaire auprès d'un large public d'architectes et d'ingénieurs de par le monde.

Cependant, en dépit du potentiel de cette typologie, très peu de projets ont vu le jour suite à la construction de la Multihalle. Il faut en effet attendre 25 ans et le développement des méthodes de calcul numérique pour voir de nouveau éclore quelques réalisations iconiques : Shigeru Ban innove en passant du bois au carton pour la construction du Pavillon de Hanovre en 2000 [3] ; puis viennent les gridshells en bois de Downland en 2002 [4] et de Savill en 2006 [5] qui reprennent fidèlement les principes développés à Mannheim mais emploient des méthodes constructives différentes. Depuis une dizaine d'années le laboratoire Navier a investi ce champ de recherche sous le double aspect de la structure et du matériau, donnant lieu à la réalisation de quelques prototypes (en 2006 et 2007 [6, 7]) et des deux premiers bâtiments de type gridshell élastique en matériau composite construits à ce jour (Solidays 2011 [8] et Créteil 2013 [9]).<sup>1</sup> Plus récemment, on a pu observer un certain engouement pour la construction de pavillons en bois de petite taille, non couverts, réalisés selon des principes similaires à ceux de la Multihalle, essentiellement dans le cadre de workshops pédagogiques ou bien de projets de recherche [10, 11, 12, 13].

Il est naturel de se demander pourquoi cette innovation prometteuse peine ainsi à essaimer ? S'il est vrai que la construction de la Multihalle de Mannheim a permis de prouver la faisabilité économique et technique du concept de gridshell élastique à grande échelle, il faut bien reconnaître que cette prouesse n'a été rendue possible qu'au terme d'un long processus de maturation pour développer et acquérir l'ensemble des compétences scientifiques, techniques, méthodologiques et humaines nécessaires à sa conception et à sa construction.<sup>2</sup>

---

1. Ici, le matériau employé, un composite à base de fibres de verre imprégnées dans une matrice polyester et obtenu par pultrusion, apporte un gain de performance très significatif par rapport au bois et permet de rester sur une conception à simple nape là où le bois aurait nécessité une grille à double nape beaucoup plus complexe à réaliser.

2. "This is not a case of a building creatively designed, but based on a support system of additive known elements. This design is the result of a symposium of creative thought in the formation, the invention of building elements with the

En vérité, une telle dépense de moyens pour développer et rassembler ces compétences ne saurait assurer la reproductibilité de cette expérience sauf en de très rares occasions et pour des projets d'exception. Par ailleurs, les techniques développées à l'époque sont pour partie tombées en désuétude (e.g. la recherche de forme par maquette physique) ou bien ont fortement évoluées voir même mutées (e.g. le calcul numérique). Des matériaux nouveaux, composites, ont vu le jour. Ils repoussent les limitations intrinsèques des matériaux usuels tel que le bois et offrent des performances techniques bien plus intéressantes pour ce type d'application (durabilité, allongement à la rupture, légèreté, résistance mécanique, fiabilité de niveau industrielle, ...). Enfin, notons que le cadre réglementaire s'est considérablement étoffé apportant aussi son lot de rigidités vis-à-vis de la pénétration des innovations dans le secteur de la construction.

Ainsi la conception des gridshells se pose-t-elle en des termes nouveaux aux architectes et ingénieurs actuels. Elle se heurte aux deux difficultés majeures suivantes :

- La première difficulté est d'ordre technique et concerne la fonctionnalisation de la structure. En effet, bien que le principe du gridshell permette de réaliser des ossatures courbes de manière optimisée, il n'en reste pas moins complexe de constituer à partir de cette résille porteuse une véritable enveloppe de bâtiment capable de répondre à un large panel de critères performantiels (tels que l'étanchéité, l'isolation thermique, l'isolation acoustique, ...) sur un support qui ne présente aucune rationalité géométrique.<sup>3</sup>
- La seconde difficulté est d'ordre théorique et concerne la mise au point d'outils et de processus de conception adaptés à l'étude de ces structures d'un genre nouveau où Architecture et Ingénierie collaborent de manière indissociable à l'identité formelle de l'ouvrage. L'inadéquation des méthodes et des outils de design actuels, orientés davantage vers la justification des ouvrages que vers leur conception, constitue un des principaux freins à la diffusion de cette innovation.

Le présent manuscrit s'articule autour de deux grandes parties qui tentent chacune de construire des éléments de réponse aux défis identifiés précédemment. La première partie, composée des chapitres 1 et 2, est destinée à présenter en profondeur le concept de gridshell

---

simultaneous integration of the theoretical, scientific contributions from mathematics, geodesy, model measuring, statics as well as control loading and calculation. We are dealing with more than pure 'teamwork', we are dealing with team creation." [Georg Lewenton 1, p. 201]

**3.** Pour contourner cette difficulté, une approche prometteuse consiste à identifier des classes de surfaces courbes (comme les maillages isoradiaux) dont certaines propriétés géométriques (e.g. facettes planes, noeuds sans torsion) s'avèrent avantageuses sur le plan constructif [14].

élastique, son potentiel et les difficultés techniques sous-jacentes (voir partie I). La seconde partie, composée des chapitres 3 à 6, est consacrée au développement d'un élément de poutre discret original prenant en compte les sollicitations de flexion et de torsion et applicable à tout type de section dont le centre de torsion est confondu avec le centre de masse, ainsi que certains types de discontinuités liées à la présence de connexions dans les résilles de type gridshell (voir partie II). Cette seconde partie constitue le coeur *académique* de ce travail de thèse.

Dans le chapitre 1 nous rappelons la genèse de cette invention et nous en donnons une définition précise et actualisée. Puis nous dressons un état des lieux critique des projets réalisés sur ce principe depuis le début des années 1960 à nos jours. Cette brève histoire des gridshells dessine à elle seule le potentiel de ces structures, notamment en terme d'expression formelle et de performance structurelle. Loin de les enfermer dans un style d'architecture particulier, elle en souligne au contraire la formidable variété. Cette revue de projet est complétée par une revue approfondie de la littérature existante sur l'ensemble des domaines connexes à cette thématique (géométrie, structure, matériaux, logiciel).

Dans le chapitre 2 nous présentons de manière détaillée la conception et la réalisation de la cathédrale éphémère de Créteil, un gridshell élastique en matériau composite construit en 2013 et toujours en service. Cette expérience peu commune a été une source inépuisable pour alimenter ce travail de thèse. Cette relecture expose les méthodes et les outils de conceptions développés pour faire aboutir le projet, les difficultés rencontrées, les pistes d'amélioration. Elle fournit également une analyse économique pour cerner les axes de progrès prioritaires dans l'optique d'une commercialisation future.

Dans le chapitre 3 nous rappelons les notions fondamentales déjà connues, indispensables à notre étude, pour la caractérisation géométrique de courbes de l'espace et de repères mobiles attachés à des courbes. Ces notions sont présentées pour le cas continu puis pour le cas discret ; ce dernier étant essentiel pour la résolution numérique de notre modèle. Cependant, nous observons que la notion clef de courbure géométrique perd son univocité dans le cas discret. Nous identifions alors plusieurs définitions de la courbure discrète. Puis nous les comparons selon des critères propres à notre application (convergence géométrique, représentativité énergétique, forme d'interpolation). A l'issue de cette analyse, la définition la plus pertinente est retenue pour le développement du nouveau modèle numérique au cours des chapitres suivants.

Dans le chapitre 4 nous élaborons un premier modèle de poutre à 4-DOFs par une approche variationnelle. Ici nous reprenons et enrichissons un travail initié lors d'une précédente thèse [15] inspirée par des travaux récents sur la simulation des tiges élastiques dans le

domaine des *computer graphics* [16], et à laquelle j'ai collaboré [17, 18]. En particulier, notre développement permet d'aboutir à des expressions purement locales des efforts internes et prouve l'équivalence avec le membre statique des équations de Kirchhoff. Sur le plan mathématique, le modèle est développé en continu et son implémentation numérique n'est pas traité.

Dans le chapitre 5 nous développons une nouvelle approche, plus directe et plus complète, pour construire à partir des équations de Kirchhoff un élément de poutre enrichi par un noeud fantôme et possédant lui aussi un nombre de degré de liberté minimal. L'originalité de cet élément est de pouvoir localiser proprement dans l'espace certains types de discontinuités, notamment des discontinuités de courbures provoquées par des efforts ponctuels ou des sauts de propriétés matérielles. Cela permet une modélisation plus fine des phénomènes physiques au sein de la grille, aussi bien au niveau des connexions que des conditions aux appuis, ce qui était le principal objectif de ce travail de thèse.

Dans le chapitre 6 nous combinons les résultats des chapitres précédents pour construire un élément de poutre discret tout à fait adapté à la modélisation numérique des gridshells élastiques. Nous présentons la construction de cet élément et la méthode de résolution numérique employée pour trouver l'état d'équilibre statique du système, à savoir le relaxation dynamique. Enfin, nous donnons quelques éléments sur *Marsupilami*, le programme informatique que nous avons mis au point et qui implémente l'élément de poutre discret élaboré au cours de cette thèse. Nous exposons aussi quelques résultats de comparaison avec des logiciels du commerce qui ont permis de valider notre travail. Plus généralement, l'élément développé convient bien pour modéliser des problèmes de couplage flexion-torsion dans des poutres élancées, comme par exemple les phénomènes de repositionnement des câbles et des gaines accrochées aux bras robots, un matériel industriel qui se démocratise à grande vitesse.



# Part I

# ELASTIC GRIDSHELL



# Chapter 1

## ELASTIC GRIDSHELLS

### 1.1 INTRODUCTION

This chapter is meant to define and introduce what elastic gridshell structures are. It develops a comprehensive but precise view of the numerous knowledge and know-how that gravitate around this concept.

#### 1.1.1 OVERVIEW

We naturally begin this chapter by defining the notion of elastic gridshell and the context in which this technology arose (see §1.2). We briefly highlight the benefits of composite materials for this kind of structure. We then propose two thorough reviews : the first one is dedicated to known built elastic gridshell structures (see §1.3) while the second one is a literature review of the main works related to the topic of elastic gridshells (see §1.4).

### 1.1.2 CONTRIBUTIONS

- We establish a chronological review of known built elastic gridshells, from the very beginning of this technology to the present time. We reveal the richness of this concept by exhibiting the great variety of realised projects. We discuss the specificities brought by each one of these projects.
- We establish an up-to-date review of the existing scientific literature, crossing multiple fields of research (geometry, mechanics, material, ...).

## 1.2 DEFINITION

The invention of the *elastic gridshell* concept is commonly attributed to Frei Otto, a German architect who devoted several years to gridshells. In 1975 he achieved the famous *Mannheim Multihalle* [2], a wooden shell of 7500 m<sup>2</sup>, in collaboration with the engineer Edmund Happold (Arup). Literally, the word “gridshell” refers to grids behaving like shells : from a mechanical point of view that means stresses acting on the structure are mainly transmitted through compression and tension. These structures can cross large-span with very little material.


However, according to the historic evolution of the concept, to characterise a gridshell as the combination of a structural concept (a grid behaving like a shell, see §1.2.2) and a specific construction process (see §1.2.1) using the bending flexibility of the material (see §1.2.3) seems to be more accurate. The project of Mannheim – in which a wooden regular and planar grid, lacking shear stiffness, is elastically deformed up to a targeted shape with the help of stays, and then braced and covered – is regarded as the starting point of this new concept (see figs. 1.1a to 1.1d).

This type of gridshell, known as elastic gridshell, offers a very elegant manner to materialise freeform shapes from an initially flat and regular grid, which obviously has many practical benefits : planar initial geometry, standard connection nodes, standard profiles and so on. Note that the term *rigid gridshell* is often opposed to the term *elastic gridshell* to indicate reticulated structures that behave like shells but are not formed in an active-bending process.


### 1.2.1 ERECTION PROCESS

Usually, the grid morphology is not trivial and leads to design numerous costly and complex joints. To overcome this issue, an original and innovative erection process was developed

1.1a



1.1b



1.1c



1.1d

- 1.1** Forming process of the gridshell of Mannheim, Germany
- 1.1a** Assembly of the timber grid
- 1.1b** Deformation of the grid
- 1.1c** Final shape of the lattice
- 1.1d** Roofing with a membrane

that takes advantage of the flexibility inherent to slender elements. A regular planar grid made of long continuous linear members is built on the ground (see fig. 1.1a). The elements are pinned together so the grid has no in-plane shear stiffness and can accommodate large-scale deformations during erection. Then, the grid is bent elastically to its final shape (see figs. 1.1b and 1.1c). Finally, the grid is frozen in the desired shape with a third layer of bracing members and the structure becomes a shell. This process is illustrated and detailed in the next chapter (see §2.3).

### 1.2.2 STRUCTURAL TYPOLOGY


Their mechanical behaviour is very similar to the one of real shells even if the material is discrete and located in a grid more or less open. Moreover, gridshells benefit from the same advantages as the ones showed by an eggshell : they can cross large span using a low amount of material. Their stiffness is mainly linked to their double-curved shape.

### 1.2.3 MATERIAL FLEXIBILITY FOR STRUCTURAL RIGIDITY

In this field of application, composite materials like glass fibre reinforced polymer (GFRP) could favourably replace wood, where both resistance and bending ability of the material is sought [7]. The stiffness of the structure does not derive from the intrinsic material rigidity but principally from its geometric curvature. Ideally, the composite profiles are produced by pultrusion, an economic continuous moulded process. The standardisation of the process guaranties very stable material and mechanical properties. It frees designers from the painful problematic of wood joining and wood durability. The characterisation of this material is presented further in the thesis (see §2.5).

## 1.3 BUILT ELASTIC GRIDSHELLS : A REVIEW

No thorough historic review is available about executed projects of elastic gridshells although some partial reviews have been done time to time on the occasion of scientific works or construction projects. This review aims at filling this gap by giving an overview of the development of the concept from the very beginning to the very last experiments. Only known built projects have been identified and reported here. The only condition for a project to belong to this review is to comply with the definition of what an elastic grid-shell is (see §1.2), independently to any other consideration (material, fabrication, size, cladding, ...).



## 1.2 Known elastic gridsells built by the past

The surface of the bubbles is proportional to the covered area. Colour indicates the material employed for the rods.

The informations collected during this research work are given in table format in appendix (see chapter A). A synthetic presentation of these datas is proposed to the reader in fig. 1.2, where projects are ordered by date, span, covered area and material.

The books edited by the *Institut für leichte Flächentragwerke* are of great interest to understand the beginnings. *IL10 Grid Shells* [19] has a precise inventory of the first experiments from 1962 to 1976, while *IL13 Multihalle Mannheim* [1] focuses on the construction of the Multihalle in Mannheim. *Timber gridshells: architecture, structure and craft* [20] is a significant effort but focuses exclusively on medium to large scale projects in timber. A small but general partial review is also available in [21]. An interesting review is also given by Quinn and Gengnagel [22] as part of their research work on new erection methods. A review of bracing and cladding systems is done in [23]. A review of form-finding methods is done in [24]. Finally, various valuable reviews are available in the thesis of Douthe [25], Bouhaya [26], Tayeb [27], and Lafuente Hernández [28].

### 1.3.1 THE BEGINNINGS : FROM THE FIRST PROTOTYPE TO THE GERMAN PAVILION

Frei Otto started his studies in architecture in 1947 in Berlin, Germany, and completed his doctorate on tensile structures in 1953. This first work was published and translated later in the 60's. He then began to work in the field of lightweight structures using physical models such as soap films or hanging nets, and photographic measurements.<sup>1,2</sup> These tools were essentials for his exploration of forms and structures as there were no computers at that time.


#### Steel Gridshell, Berkeley, USA, 1962

Simultaneously, he became interested by the study of lightweight shells and the way they were form-found. One of his very first elastic gridshell was built in 1962 with students at Berkeley, USA [19, p. 270]. It is funny to remark that this first gridshell was not a timber gridshell but a steel gridshell made out of twin steel rods linked in a grid fashion by bolts with clamping plates (see fig. 1.3a). This first experiment demonstrated at small scale the

---


1. In the 19<sup>th</sup> and 20<sup>th</sup> centuries model testing was at the heart of structural innovation [29]. Analog models were employed successfully by well-known architects and engineers to go beyond the limits of existing knowledge (A. Gaudi, H. Isler, F. Candela, F. Otto, ...) and are still employed today where numeric models failed to represent accurately some physical phenomenons (for instance in wind analysis for high rise towers and bridges).

2. "Photography is the medium through which the form and content of a model are communicated. It is one of our most important tools in that it provides the basis for documentation and information, supplements our creative potential [...]" [19, p. 56]




1.3b

1.3a



1.4



1.5

- 1.3** Steel gridshell built in 1962 in Berkeley, USA
- 1.3a** Steel lattice
- 1.3b** Knot detail
- 1.4** Timber gridshell built in 1962 in Essen, Germany
- 1.5** Timber gridshell built in 1967 in Montreal, Canada

ability to bend a regular grid with no shear rigidity into a curved shape (see fig. 1.3b). The grid was loosely braced and shell effects were not investigated.

### **Essen Gridshell, Essen, Germany, 1962**

The same year he designed and built a first timber gridshell in Essen, Germany [19, p. 272]. The prototype – a single-layer gridshell spanning 17 m and covering an area of 198 m<sup>2</sup> – was made with 3-ply laminated timber profiles in hemlock pine (see fig. 1.4). The cross-section of the profiles was rectangular (60 mm x 40 mm) and the elements were assembled in a grid fashion with simple steel bolts. Once erected, nothing was specifically done to improve the in-plane shear stiffness of the grid and activate a shell behaviour. Finally, the structure was covered with a transparent plastic foil nailed directly on the grid's profiles.

### **German Pavilion Auditoria, Montreal, Canada, 1967**

Five years later, on the occasion of the *1967 International and Universal Exposition* in Montreal, Canada, Frei Otto was appointed to design the German Pavilion : a large cable net tent prefiguring the realisation of the olympic stadium of Munich, Germany, in 1972.<sup>3,4</sup> The pavilion required two auditoria and these were designed using the principle of elastic gridshell [19, p. 274]. All together, the auditoria covered an area of 365 m<sup>2</sup> and spanned 17.5 m. The construction technique employed in Montreal was quite similar to the one developed in Essen, but this time the grid was fully braced with a layer of nailed plywood boards and offered a proper roofing made out of insulation panels covered with a PVC coated fabric (see fig. 1.5).

The two gridshells built in Montreal mark a significant step in the maturation process of the technique leading to the major realisation of Mannheim in 1976 : a methodology has emerged to progress “from the inverted form to the gridshell” [19, p. 179] ; main construction details have been validated ; various erection methods have been tested ; mid-scale buildings have been built to host public. However, due to the over complexity of these structures, lots of unknowns remained unsolved at this stage and the behaviour of the structures could not be fully predicted.<sup>5</sup>

---

3. Actually, Frei Otto became the director of the newly founded *Institute for Lightweight Structures* (Institut für Leichte Flächentragwerke or IL) at the University of Stuttgart in 1964. It was the IL that was commissioned by the German government to conduct research in connection with the planning of the German pavilion for the exposition in Montreal.

4. Video of the construction of the German pavilion : <https://www.youtube.com/watch?v=Z0mtFMoseUk>.

5. “Snow accumulations in the throat of the common edge beam probably caused one of the two grid shells of project Montreal to buckle in a relatively flat region. The diameter of the buckled area was about 3 meters. Neither grid rod was

It is worthwhile to mention that several unexecuted large-scale projects were studied by Frei Otto between 1967 and 1973 at the *IL* or at the *Atelier Warmbronn*.<sup>6</sup> These projects are basically documented in [19, pp. 278 - 288] and reveal that he was training his capacity to master large-scale projects with the technique of elastic gridshells for more conventional building projects (wave pool, swimming hall, multi-purpose hall, auditorium, ...).

### 1.3.2 MANNHEIM MULTIHALLE : THE COMPLETION OF A DECADE OF RESEARCH

The project of the Multihalle started in 1970, when the decision was made that Mannheim, Germany, would hold the Bundesgartenschau in 1975.<sup>7</sup> The architects of the project, *Carl Mutschler & Partners*, consulted Frei Otto at *Atelier Warmbronn* as he was starting to get known in the field of innovative lightweight structures. This is how the idea of the gridshell was introduced in the project [30].

A thorough report on the project is available in [1]. A more condensed but still precise description of the engineering problematics related to this project are available in the excellent papers from Happold and Liddell [2] and Liddell [30].

#### Multihalle, Mannheim, Germany, 1975

Mannheim is an unprecedented realisation because it is more than twenty times larger than the previously built gridshells in Montreal and is meant to last many years and not only for the duration of a short-term exhibition. The timber lattice, still existing in 2017, covers an area of 7400 m<sup>2</sup> (see fig. 1.6a). It is composed of two interconnected domes, one for the multi-purpose hall (span : 60 m | height : 20 m) and one for the restaurant (span : 50 m | height : 18 m).

Although the constructive system deployed in Mannheim clearly inherited from the previous developments, the challenge was such that it had to be revisited. In particular the main additions were the introduction of the double-layer system and the proper bracing of the grid. A major advance was also the use of the very first numeric models to study the structure.

The double-layer system was introduced to tackle two issues : the grid needed some flexibility to be bent into the desired shape, but once erected it should provide sufficient

---

broken, i.e. the buckling progressed elastically. It might have been possible to press the buckled area back into shape." [19, p. 219]

6. Atelier Warmbronn is the architectural studio founded by Frei Otto in 1969.

7. The Bundesgartenschau is a national horticultural exhibition that takes place every two years in Germany.



1.6a

bending stiffness to resist disturbing loads and avoid a buckling collapse.<sup>8</sup> Once erected, the two grids, one sliding on top of the other one, were connected together to form a single grid with much higher ladder profiles (from 50 mm to 150 mm), increasing their bending stiffness by a factor of about 26 (see fig. 1.6b).

Because the in-plane stiffness of the grid also plays a major role in the resistance to buckling, this question was considered with care. The bracing of the grid was first achieved by preventing the nodes to turn once the grid was erected. This was done by creating some friction in the nodes when tightening the bolts linking the laths, after the grid was erected. Then, additional bracing cables were put in the grid.

---

**8.** Theoretically, self-weight loads would produce only compression in the members because the (funicular) form of the grid resulted from the inversion of a hanging chain model in pure tension.



1.6b



**1.6** Timber gridshell built in 1975 in Mannheim, Germany  
**1.6a** Sky view  
**1.6b** Interior view

Finally, the project of Mannheim was a key project in the development of modern lightweight structures. Great engineers were born in touch with Frei Otto, following his footsteps or collaborating with him. This heritage has irrigated for several decades the engineering of lightweight structures in Europe and gave birth, directly or indirectly, to several studios among which we can cite *Buro Happold* and *Schlaich Bergermann & Partner*.

### 1.3.3 THE DRY PERIOD : 25 YEARS FROM MANNHEIM TO HANNOVER

Although the experience of Mannheim proved the feasibility and the potential of gridshell structures for large-scale projects, it also revealed that these projects were subject to an incredible complexity in terms of structural design, geometry, modelling, testing, team work, construction methods ... At that time, very few people could pretend to master all the knowledge and techniques required to design and built timber gridshells and developed in the bosom of the *Institute for Lightweight Structures* in Stuttgart.

This project was obviously well ahead of its time and the engineering cost to design such structures was probably prohibitive considering the tools available at that time. This certainly explains why no elastic gridshells were built during the 25 following years, despite the optimism of the pioneers of the Multihalle.<sup>9</sup>

Note that around 1975 small workshop and experiments lead to the construction of several but small elastic gridshells, as reported in [19]. A non-exhaustive but quite extensive list of known executed gridshell projects is presented in fig. 1.2. The dry period is clearly visible.

### 1.3.4 THE SIGNS OF A RENEWAL : DORSET AND DONCASTER

It is only 20 years later that gridshells started to reappear, in the late 90's mainly in the United Kindom, and for projects that had interest in environmental problematics.

#### *Westminster Lodge, Dorset, England, 1995*

In 1995, a small student residence named *Westminster Lodge* was built in Dorset, England. This dwelling was part of a larger project – Hooke Park – aiming at investigating how the local forest resources, in particular immature roundwood thinnings, could be better

---

9. "For many years after its completion, Happold promoted the benefit of the timber gridshell as a construction technique and stated that he could not understand why it had not been adopted more widely. He perceived the benefits to be in the efficiency of the construction method to enable doubly curved (shell) structures to be constructed quickly and cost effectively." [31].

1.7a



1.7b



1.8a



1.8b

**1.7** Roundwood gridshell built in 1995 in Dorset, England

**1.7a** Interior view

**1.7b** Exterior view

**1.8** Timber gridshells built in 1998 in Doncaster, England

**1.8a** Interior view

**1.8b** Exterior view



# BIBLIOGRAPHY

- 1 F. Otto, “IL13 Multihalle Mannheim,” B. Burkhardt, M. Chaitos, J. Langner, W. Langner and G. Lubberger, Eds., ser. Institut für leichte Flächentragwerke (IL). Stuttgart, 1978.
- 2 E. Happold and I. Liddell, “Timber lattice roof for the Mannheim bundesgartenschau,” *The Structural Engineer*, vol. 53, no. 3, pp. 99–135, 1975.
- 3 M. McQuaid, F. Otto and S. Ban, “Engineering and Architecture: building the Japan pavilion,” in *Shigeru Ban*, Phaidon Press, 2006, pp. 8–11.
- 4 R. Harris and O. Kelly, “The structural engineering of the Downland gridshell,” in *Space Structures 5*, vol. 1, 2002, pp. 161–172.
- 5 R. Harris, S. Haskins and J. Roynon, “The Savill Garden gridshell: design and construction,” *The Structural Engineer*, vol. 86, no. 17, pp. 27–34, 2008.
- 6 C. Douthe, O. Baverel and J.-F. Caron, “Form-finding of a grid shell in composite materials,” *Journal of the International Association for Shell and Spatial Structures*, vol. 47, no. 1, pp. 53–62, 2006.
- 7 C. Douthe, J.-F. Caron and O. Baverel, “Gridshell structures in glass fibre reinforced polymers,” *Construction and Building Materials*, vol. 24, no. 9, pp. 1580–1589, 2010.

- 8 O. Baverel, J.-F. Caron, F. Tayeb and L. du Peloux, "Gridshells in composite materials: construction of a 300m<sup>2</sup> forum for the Solidays' festival in Paris," *Structural Engineering International*, vol. 22, no. 3, pp. 408–414, 2012.
- 9 L. du Peloux, F. Tayeb, O. Baverel and J.-F. Caron, "Construction of a large composite grid-shell tructure: a lightweight structure made with pultruded glass fibre reinforced polymer tubes," *Structural Engineering International*, vol. 26, no. 2, pp. 160–167, 2016.
- 10 B. D'Amico, A. Kermani and H. Zhang, "Form finding and structural analysis of actively bent timber grid shells," *Engineering Structures*, vol. 81, pp. 195–207, 2014.
- 11 D. Naicu, R. Harris and C. Williams, "Timber gridshells: design methods and their application to a temporary pavilion," in *World Conference on Timber Engineering*, Quebec City, Canada, 2014.
- 12 B. D'Amico, A. Kermani, H. Zhang, A. Pugnale, S. Colabella and S. Pone, "Timber gridshells: numerical simulation, design and construction of a full scale structure," *Structures*, vol. 3, pp. 227–235, 2015.
- 13 J. Haddal Mork, S. Dyvik Hillersøy, B. Manum, A. Rønnquist and N. Labonnote, "Introducing the segment lath - A simplified modular timber gridshell built in Trondheim Norway," in *World Conference on Timber Engineering*, Vienna, Austria, 2016.
- 14 R. Mesnil, "Structural explorations of fabrication-aware design spaces for non-standard architecture," PhD thesis, Université Paris-Est, 2017.
- 15 F. Tayeb, B. Lefevre, O. Baverel, J.-F. Caron and L. du Peloux, "Design and realisation of composite gridshell structures," *Journal of the International Association for Shell and Spatial Structures*, vol. 56, no. 1, pp. 49–59, 2015.
- 16 M. Bergou, M. Wardetzky, S. Robinson, B. Audoly and E. Grinspun, "Discrete elastic rods," *ACM Transactions on Graphics*, vol. 27, no. 3, 63:1–63:12, 2008.
- 17 L. du Peloux, F. Tayeb, B. Lefevre, O. Baverel and J.-F. Caron, "Formulation of a 4-DoF torsion/bending element for the formfinding of elastic gridshells," in *Proceedings of the IASS Annual Symposium*, Amsterdam, Netherlands, 2015.
- 18 B. Lefevre, F. Tayeb, L. du Peloux and J.-F. Caron, "A 4-degree-of-freedom Kirchhoff beam model for the modeling of bending–torsion couplings in active-bending structures," *International Journal of Space Structures*, vol. 32, no. 2, pp. 69–83, 2017.
- 19 F. Otto, "IL10 Grid Shells," B. Burkhardt, J. Henniecke and E. Schauer, Eds., ser. Institut für leichte Flächentragwerke (IL). Stuttgart, 1974.
- 20 J. Chilton and G. Tang, "Timber gridshells: architecture, structure and craft." Routledge, 2017.
- 21 M. Collins and T. Cosgrove, "A Review of the state of the art of timber gridshell design and construction," in *Civil Engineering Research in Ireland*, 2016.
- 22 G. Quinn and C. Gengnagel, "A review of elastic grid shells, their erection methods and the potential use of pneumatic formwork," in *WIT Transactions on the Built Environment*, vol. 136, Jun. 2014, pp. 129–143.

- 23 P. Cuvilliers, C. Douthe, L. du Peloux and R. Le Roy, "Hybrid structural skin: prototype of a GFRP elastic gridshell braced by a fibre-reinforced concrete envelope," *Journal of the International Association for Shell and Spatial Structures*, vol. 58, no. 1, pp. 65–78, 2017.
- 24 L. Kim-Lan Vaultot, "Form-finding of elastic gridshells," MSc thesis, MIT, 2016.
- 25 C. Douthe, "Etude de structures élancées précontraintes en matériaux composites : application à la conception des gridshells," PhD thesis, Ecole Nationale des Ponts et Chaussées, 2007.
- 26 L. Bouhaya, "Optimisation structurelle des gridshells," PhD thesis, Université Paris-Est, 2010.
- 27 F. Tayeb, "Simulation numérique du comportement mécanique non linéaire de gridshells composés de poutres élancées en matériaux composites et de sections quelconques," PhD thesis, Université Paris-Est, 2015.
- 28 E. Lafuente Hernández, "Design and optimisation of elastic gridshells," PhD thesis, Universität der Künste Berlin, 2015.
- 29 B. Addis, "Toys that save millions - A history of using physical models in structural design," *The Structural Engineer*, vol. 91, no. 4, pp. 12–27, 2013.
- 30 I. Liddell, "Frei Otto and the development of gridshells," *Case Studies in Structural Engineering*, vol. 4, no. Supplement C, pp. 39–49, 2015.
- 31 R. Harris, J. Romer, O. Kelly and S. Johnson, "Design and construction of the Downland gridshell," *Building Research and Information*, vol. 31, no. 6, pp. 427–454, 2003.
- 32 R. Burton, M. Dickson and R. Harris, "The use of roundwood thinnings in buildings: a case study," *Building Research and Information*, vol. 26, no. 2, pp. 76–93, 1998.
- 33 O. Lowenstein, "Lothian Gridshell," *Building for a Future Winter*, pp. 22–29, Mar. 2002.
- 34 Bdonline.co.uk, "The other gridshell," 2002.
- 35 O. Lowenstein, "Gridshells in England. Ideas from the U.K. make stunning use of small timber," *Wood Design and Building*, May 2004.
- 36 Fourthdoor.org, "Growing and making Flimwell's chestnut gridshell," 2003.
- 37 "The Savill building. A visitor centre with a timber gridshell roof gridshell structures," *TRADA*, pp. 1–7, 2006.
- 38 N. Labonnote, J. H. Mork, S. H. Dyvik, A. Rønnquist and B. Manum, "Experimental and numerical study of the structural performance of a timber gridshell," in *World Conference on Timber Engineering*, Vienna, Austria, 2016, pp. 3–10.
- 39 S. Adriaenssens, "Stressed spline structures," PhD thesis, University of Bath, 2000.
- 40 S. Adriaenssens, M. Barnes and C. Williams, "A new analytic and numerical basis for the form-finding and analysis of spline and gridshell structures," in *Computing Developments in Civil and Structural Engineering*, B. Kumar and B. H. V. Topping, Eds., Edinburgh: Civil-Comp Press, 1999, pp. 83–91.

- 41 M. Barnes, "Form finding and analysis of tension structures by dynamic relaxation," *International Journal of Space Structures*, vol. 14, no. 2, pp. 89–104, 1999.
- 42 S. Adriaenssens and M. Barnes, "Tensegrity spline beam and grid shell structures," *Engineering Structures*, vol. 23, no. 1, pp. 29–36, 2001.
- 43 M. Barnes, S. Adriaenssens and M. Krupka, "A novel torsion/bending element for dynamic relaxation modeling," *Computers and Structures*, vol. 119, pp. 60–67, 2013.
- 44 E. Poulsen, "Structural design and analysis of elastically bent gridshells: the development of a numerical simulation tool," MSc thesis, Chalmers University of Technology, 2015.
- 45 B. D'Amico, H. Zhang and A. Kermani, "A finite-difference formulation of elastic rod for the design of actively bent structures," *Engineering Structures*, vol. 117, pp. 518–527, 2016.
- 46 J. Bessini, C. Lázaro and S. Monleón, "A form-finding method based on the geometrically exact rod model for bending-active structures," *Engineering Structures*, vol. 152, pp. 549–558, 2017.
- 47 T. Bulenda and J. Knippers, "Stability of grid shells," *Computers and Structures*, vol. 79, no. 12, pp. 1161–1174, 2001.
- 48 R. Mesnil, J. Ochsendorf and C. Douthe, "Stability of pseudo-funicular elastic grid shells," *International Journal of Space Structures*, vol. 30, no. 1, pp. 27–36, 2015.
- 49 B. Lefevre, C. Douthe and O. Baverel, "Buckling of elastic gridshells," *Journal of the International Association for Shell and Spatial Structures*, vol. 56, no. 185, pp. 153–171, 2015.
- 50 S. R. Malek, "The effect of geometry and topology on the mechanics of grid shells," PhD thesis, MIT, 2012.
- 51 T. Jensen, O. Baverel and C. Douthe, "Morphological and mechanical investigation of interconnected elastic gridshells," *International Journal of Space Structures*, vol. 28, no. 3-4, pp. 175–186, 2013.
- 52 G. Filz and D. Naicu, "2 Landscapes – interaction of 2 gridshells based on a modified Stewart-Gough principle," in *Proceedings of the IASS Working Groups 12 + 18 International Colloquium*, Tokyo, Japan, 2015.
- 53 F. Tayeb, J.-F. Caron, O. Baverel and L. du Peloux, "Stability and robustness of a 300m<sup>2</sup> composite gridshell structure," *Construction and Building Materials*, vol. 49, pp. 926–938, 2013.
- 54 M. Toussaint, "A design tool for timber gridshells: the development of a grid generation tool," MSc thesis, Delft University of Technology, 2007.
- 55 J. Olsson, "Form finding and size optimization: Implementation of beam elements and size optimization in real time," MSc thesis, Chalmers University of Technology, 2012.
- 56 L. Bouhaya, O. Baverel and J.-F. Caron, "Mapping two-way continuous elastic grid on an imposed surface: application to grid shells," in *Proceedings of the IASS Annual Symposium*, Valencia, Spain, 2009, pp. 989–997.

- 57 L. Bouhaya, O. Baverel and J.-F. Caron, "Optimization of gridshell bar orientation using a simplified genetic approach," *Structural and Multidisciplinary Optimization*, vol. 50, no. 5, pp. 839–848, 2014.
- 58 E. Lafuente Hernández, S. Sechelmann, T. Rörig and C. Gengnagel, "Topology optimisation of regular and irregular elastic gridshells by means of a non-linear variational method," in *Advances in Architectural Geometry*, 2012, pp. 147–160.
- 59 L. du Peloux, O. Baverel, J.-F. Caron and F. Tayeb, "From shape to shell: a design tool to materialize freeform shapes using gridshell structures," in *Design Modeling Symposium*, Berlin, Deutschland, 2011.
- 60 Y. Masson and L. Monasse, "Existence of global Chebyshev nets on surfaces of absolute Gaussian curvature less than  $2\pi$ ," *Journal of Geometry*, vol. 108, no. 1, pp. 25–32, 2017.
- 61 Y. Masson, "Existence et construction de réseaux de Chebyshev avec singularités et application aux gridshells," PhD thesis, Université Paris-Est, 2017.
- 62 S. Pone, G. Mirra, E. Pignatelli, D. Lancia and S. Colabella, "Specialised algorithms for different project stages in a post-formed timber gridshell design," in *Proceedings of the 3rd International Conference on Structures and Architecture*, Guimarães, Portugal, 2016, pp. 259–266.
- 63 C. Douthe, R. Mesnil, H. Orts and O. Baverel, "New shapes for elastic gridshells covered by planar facets," in *Proceedings of the IASS Annual Symposium*, Tokyo, Japan, 2016, pp. 1–9.
- 64 N. Kotelnikova-Weiler, C. Douthe, E. Lafuente Hernández, O. Baverel, C. Gengnagel and J.-F. Caron, "Materials for actively-bent structures," *International Journal of Space Structures*, vol. 28, no. 3-4, pp. 229–240, 2013.
- 65 N. Kotelnikova-Weiler, "Optimisation mécanique et énergétique d'enveloppes en matériaux composites pour les bâtiments," PhD thesis, Université Paris-Est, 2012.
- 66 G. Quinn, C. Gengnagel and K.-U. Bletzinger, "Simulating pneumatic erection of strained grid shells via dynamic relaxation," in *Proceedings of the IASS Annual Symposium*, Tokyo, Japan, 2016.
- 67 A. Liuti, A. Pugnale and B. D'Amico, "Building timber gridshells with air: numerical simulations and technique challenges," in *Proceedings of the 3rd International Conference on Structures and Architecture*, Guimarães, Portugal, 2016, pp. 251–258.
- 68 E. L. Hernández and C. Gengnagel, "A new hybrid: elastic gridshells braced by membranes," in *WIT Transactions on the Built Environment*, vol. 136, Jun. 2014, pp. 157–169.
- 69 B. D'Amico, A. Kermani, H. Zhang, P. Sheperd and C. Williams, "Optimisation of cross-section of actively bent grid shells with strength and geometric compatibility constraints," *Computers and Structures*, vol. 154, pp. 163–176, 2015.
- 70 A. Menges, O. D. Krieg and T. Schwinn, Eds., "Advancing wood architecture: a computational approach." Routledge, 2016.
- 71 Site Sécurité, "Règlement ERP type CTS (big tops & tents)."

- 72** J. L. Clarke, “Eurocomp design code and handbook: structural design of polymer composites,” J. L. Clarke, Ed. E & FN Spon, 2003.
- 73** L. C. Bank, “Composites for construction: structural design with FRP materials.” John Wiley & Sons, 2006.
- 74** Fiberline Composites A/S, “Fiberline design manual,” 2nd ed. 2002.
- 75** C. Douthe, I. Stefanou and S. Geng, “Long term behaviour of prestressed composite pipes,” in *20èmes Journées Nationales sur les Composites*, 2017, pp. 1399–1406.
- 76** G. F. A. L’Hospital, “Analyse des infiniment petits, pour l’intelligence des lignes courbes.” A Paris, de l’Imprimerie royale, 1696.
- 77** J. Delcourt, “Analyse et géométrie, histoire des courbes gauches de Clairaut à Darboux,” *Archive for History of Exact Sciences*, vol. 65, no. 3, pp. 229–293, 2011.
- 78** T. Hoffmann, “Discrete differential geometry of curves and Surfaces,” in *Math-for-Industry Lecture Note Series*, vol. 18, 2009.
- 79** E. Vouga, “Plane curves,” in *Lectures in Discrete Differential Geometry*, Austin, USA, 2014, ch. 1.
- 80** R. Bishop, “There is more than one way to frame a curve,” *The American Mathematical Monthly*, vol. 82, no. 3, pp. 246–251, 1975.
- 81** F. Klok, “Two moving coordinate frames for sweeping along a 3D trajectory,” *Computer Aided Geometric Design*, vol. 3, no. 3, pp. 217–229, 1986.
- 82** H. Guggenheimer, “Computing frames along a trajectory,” *Computer Aided Geometric Design*, vol. 6, no. 1, pp. 77–78, 1989.
- 83** J. Bloomenthal, “Calculation of reference frames along a space curve,” in *Graphics Gems*, A. S. Glassner, Ed., vol. 1, San Diego, USA: Academic Press Professional, Inc., 1990, pp. 567–571.
- 84** A. J. Hanson and H. Ma, “Parallel transport approach to curve framing,” Indiana University, Bloomington, USA, Tech. Rep., 1995.
- 85** T. Poston, S. Fang and W. Lawton, “Computing and approximating sweeping surfaces based on rotation minimizing frames,” in *Proceedings of the 4th International Conference on CAD/CG*, Wuhan, China, 1995.
- 86** W. Wang, B. Jüttler, D. Zheng and Y. Liu, “Computation of rotation minimizing frames,” *ACM Transactions on Graphics*, vol. 27, no. 1, 2:1–2:18, 2008.
- 87** R. T. Farouki, C. Giannelli, M. L. Sampoli and A. Sestini, “Rotation-minimizing osculating frames,” *Computer Aided Geometric Design*, vol. 31, no. 1, pp. 27–42, 2014.
- 88** F. Frenet, “Sur les courbes à double courbure,” *Journal de Mathématiques Pures et Appliquées*, vol. 17, no. 1, pp. 437–447, 1852.
- 89** J. Delcourt, “Analyse et géométrie : les courbes gauches de Clairaut à Serret,” PhD thesis, Université Paris-VI, 2007.

- 
- 90 J. Bernoulli, “Quo continentur Anekdotæ,” in *Opera omnia, tam antea sparsim edita, quam hactenus inedita*, 4, Marci-Michaelis Bousquet, Lausannae & Genevae, 1742.
- 91 H. Pitot, “Sur la quadrature de la moitié d’une courbe, qui est la compagne de la cycloïde,” *Histoire de l’Académie Royale des Sciences*, vol. 1, pp. 65–67, 1724.
- 92 J. L. Coolidge, “A history of geometrical methods,” ser. Dover Books on Mathematics. Oxford: Oxford, Clarendon press, 2013.
- 93 G. Monge, “Application de l’analyse à la géométrie, à l’usage de l’Ecole impériale polytechnique,” 4th ed. Paris: Ve Bernard, 1809.
- 94 L. Euler, “De motu turbinatorio, chordarum musicarum,” in *Novi Commentarii Academiae Scientiarum Imperialis Petropolitanae*, vol. 19, Petropoli, 1775, pp. 340–370.
- 95 A. Gray, E. Abbena and S. Salamon, “Modern differential geometry of curves and surfaces with Mathematica,” 3rd ed. Chapman & Hall/CRC, 2006.
- 96 D. Carroll, E. Hankins, E. Kose and I. Sterling, “A survey of the differential geometry of discrete curves,” *The Mathematical Intelligencer*, vol. 36, no. 4, pp. 28–35, 2014.
- 97 A. Bobenko, “Discrete differential geometry,” 2nd ed. 2015.
- 98 P. Romon, “Courbes discrètes planes,” ser. Références sciences. Ellipses, 2013, ch. 1.
- 99 M. Bergou, B. Audoly, E. Vouga, M. Wardetzky and E. Grinspun, “Discrete viscous threads,” *ACM Transactions on Graphics*, vol. 29, no. 4, 116:1–116:10, 2010.
- 100 J. Langer and D. A. Singer, “Lagrangian aspects of the Kirchhoff elastic rod,” *SIAM Review*, vol. 38, no. 4, pp. 605–618, Dec. 1996.
- 101 S. Nabaei, “Mechanical form-finding of timber fabric structures,” PhD thesis, EPFL, 2014.
- 102 M. Grégoire and E. Schömer, “Interactive simulation of one-dimensional flexible parts,” *Computer-Aided Design*, vol. 39, no. 8, pp. 694–707, 2007.
- 103 A. Theetten, L. Grisoni, C. Andriot and B. Barsky, “Geometrically exact dynamic splines,” *Computer-Aided Design*, vol. 40, no. 1, pp. 35–48, 2008.
- 104 F. Bertails, B. Audoly, M.-P. Cani, B. Querleux, F. Leroy and J.-L. Lévêque, “Super-helices for predicting the dynamics of natural hair,” *ACM Transactions on Graphics*, vol. 25, no. 3, pp. 1180–1187, 2006.
- 105 F. Bertails, “Super-clothoids,” *Computer Graphics Forum*, vol. 31, no. 2, pp. 509–518, 2012.
- 106 J. Spillmann and M. Teschner, “CORDE : cosserat rod elements for the dynamic simulation of one-dimensional elastic objects,” in *Eurographics Symposium on Computer Animation*, San Diego, USA, 2007, pp. 1–10.
- 107 P. Jung, S. Leyendecker, J. Linn and M. Ortiz, “A discrete mechanics approach to Cosserat rod theory Part 1: static equilibria,” *International Journal for Numerical Methods in Engineering*, vol. 85, no. 1, pp. 31–60, 2010.

- 108 F. B. Fuller, "Decomposition of the linking number of a closed ribbon: a problem from molecular biology," in *Proceedings of the National Academy of Sciences of the USA*, vol. 75, 1978, pp. 3557–3561.
- 109 A. C. Maggs, "Writhing geometry at finite temperature: Random walks and geometric phases for stiff polymers," *The Journal of Chemical Physics*, vol. 114, no. 13, pp. 5888–5896, Apr. 2001.
- 110 R. de Vries, "Evaluating changes of writhe in computer simulations of supercoiled DNA," *The Journal of Chemical Physics*, vol. 122, no. 6, 064905:1–064905:5, 2005.
- 111 M. A. Berger, "Topological quantities: calculating winding, writhing, linking, and higher order invariants," in *Lectures on Topological Fluid Mechanics, Lecture Notes in Mathematics*, vol. 1973, Springer, Berlin, Heidelberg, 2009, ch. Lecture No, pp. 75–97.
- 112 J. Alexander and S. Antman, "The ambiguous twist of love," *Quarterly of Applied Mathematics*, vol. 40, no. 1, pp. 83–92, 1982.
- 113 B. Audoly and Y. Pomeau, "Elasticity and geometry." Oxford University Press, 2010.
- 114 E. H. Dill, "Kirchhoff's theory of rods," *Archive for History of Exact Sciences*, vol. 44, no. 1, pp. 1–23, 1992.
- 115 S. Antman, "Nonlinear problems of elasticity," 2nd ed., ser. Applied Mathematical Sciences. New York: Springer, New York, NY, 2005.
- 116 E. Reissner, "On one-dimensional large-displacement finite-strain beam theory," *Studies in Applied Mathematics*, vol. 52, no. 2, pp. 87–95, 1973.
- 117 A. Love, "A treatise on the mathematical theory of elasticity," 2nd ed. Cambridge University Press, 1906.
- 118 G. Kirchhoff, "Über das gleichgewicht und die bewegung einer elastischen scheibe," *Journal für die reine und angewandte Mathematik*, vol. 1850, no. 40, pp. 51–88, 1850.
- 119 G. Kirchhoff, "Vorlesungen über mathematische Physik: Mechanik." B. G. Teubner (Leipzig), 1876.
- 120 A. Clebsch, "Théorie de l'élasticité des corps solides." Paris: Paris Dunod, 1883.
- 121 S. Neukirch, "Enroulement, contact et vibrations de tiges élastiques," Thèse d'HDR, Université Paris-VI, 2009.
- 122 S. Timoshenko, "LXVI. On the correction for shear of the differential equation for transverse vibrations of prismatic bars," *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, vol. 41, no. 245, pp. 744–746, 1921.
- 123 J. C. Simo and L. Vu-Quoc, "A Geometrically-exact rod model incorporating shear and torsion-warping deformation," *International Journal of Solids and Structures*, vol. 27, no. 3, pp. 371–393, 1991.
- 124 S. Antman, "Kirchhoff's problem for nonlinearly elastic rods," *Quarterly of Applied Mathematics*, vol. 32, no. 3, pp. 221–240, 1974.

- 125 D. Q. Cao and R. W. Tucker, “Nonlinear dynamics of elastic rods using the Cosserat theory: Modelling and simulation,” *International Journal of Solids and Structures*, vol. 45, no. 2, pp. 460–477, 2008.
- 126 H. Lang and J. Linn, “Lagrangian field theory in space and time for geometrically exact Cosserat rods,” Fraunhofer ITWM, Tech. Rep., 2009.
- 127 J. E. Cisternas and P. Holmes, “Buckling of extensible thermoelastic rods,” *Mathematical and Computer Modelling*, vol. 36, no. 3, pp. 233–243, 2002.
- 128 D. Moulton, T. Lessinnes and A. Goriely, “Morphoelastic rods. Part I: A single growing elastic rod,” *Journal of the Mechanics and Physics of Solids*, vol. 61, no. 2, pp. 398–427, 2013.
- 129 C. Lázaro, S. Monleón, J. Bessini and J. Casanova, “A review on geometrically exact models for very flexible rods,” in *Proceedings of the IASS Annual Symposium*, Tokyo, Japan, 2016.
- 130 Y. Shi, A. E. Borovik and J. E. Hearst, “Elastic rod model incorporating shear and extension, generalized nonlinear Schrödinger equations, and novel closed-form solutions for supercoiled DNA,” *The Journal of Chemical Physics*, vol. 103, no. 8, pp. 3166–3183, 1995.
- 131 B. D. Coleman, E. H. Dill, M. Lembo, Z. Lu and I. Tobias, “On the dynamics of rods in the theory of Kirchhoff and Clebsch,” *Archive for Rational Mechanics and Analysis*, vol. 121, no. 4, pp. 339–359, 1993.
- 132 R. Casati and F. Bertails, “Super space clothoids,” *ACM Transactions on Graphics*, vol. 32, no. 4, p. 1, Jul. 2013.
- 133 A. Campanile, M. Mandarino, V. Piscopo and A. Pranzitelli, “On the exact solution of non-uniform torsion for beams with asymmetric cross-section,” *World Academy of Science, Engineering and Technology*, vol. 31, pp. 36–45, 2009.
- 134 L. Prandtl, “Zur torsion von prismatischen stäben,” *Physikalische Zeitschrift*, vol. 4, pp. 758–770, 1903.
- 135 K. Koohestani, “Nonlinear force density method for the form-finding of minimal surface membrane structures,” *Communications in Nonlinear Science and Numerical Simulation*, vol. 19, no. 6, pp. 2071–2087, 2014.
- 136 S. Timoshenko and J. N. Goodier, “Theory of elasticity,” 2nd ed. McGraw-Hill Book, 1951.
- 137 S. P. Timoshenko, “Theory of bending, torsion and buckling of thin-walled members of open cross section,” *Journal of the Franklin Institute*, vol. 239, no. 4, pp. 201–219, Mar. 1945.
- 138 V. Z. Vlasov, “Thin-walled elastic beams,” 2nd ed. Israel Program for Scientific Translations, 1961.
- 139 E. Elter, “Two formulí of the shear center,” *Periodica Polytechnica Mechanical Engineering*, vol. 28, no. 2-3, pp. 179–193, 1984.
- 140 J. M. Alves, “Dynamic analysis of bridge girders subjected to moving loads : Numerical and analytical beam models considering warping effects,” MSc thesis, Técnico Lisboa, 2014.

- 141** A. Day, "An Introduction to dynamic relaxation," *The Engineer*, vol. 219, no. 5688, pp. 218–221, 1965.
- 142** J. R. H. Otter, A. C. Cassel and R. E. Hobbs, "Dynamic Relaxation," *Proceedings of the Institution of Civil Engineers*, vol. 35, no. 4, pp. 633–656, 1966.
- 143** A. C. Cassel and R. E. Hobbs, "Numerical stability of dynamic relaxation analysis of non-linear structures," *Numerical Methods in Engineering*, vol. 10, no. 6, pp. 1407–1410, 1976.
- 144** M. Barnes, "Applications of dynamic relaxation to the topological design and analysis of cable, membrane and pneumatic structures," in *International Conference on Space Structures*, Guildford, England, 1975, pp. 211–219.
- 145** M. Papadrakakis, "A method for the automatic evaluation of the dynamic relaxation parameters," *Computer Methods in Applied Mechanics and Engineering*, vol. 25, no. 1, pp. 35–48, 1981.
- 146** P. Underwood, "Dynamic relaxation," in *Computational methods for transient analysis*, 1983, ch. 5, pp. 246–265.
- 147** M. Barnes, "Form finding and analysis of tension space structures by dynamic relaxation," PhD thesis, City University of London, 1977.
- 148** D. Wakefield, "Dynamic relaxation analysis of pretensioned networks supported by compression arches," PhD thesis, City University of London, 1980.
- 149** J. Rodriguez, G. Rio, J. M. Cadou and J. Troufflard, "Numerical study of dynamic relaxation with kinetic damping applied to inflatable fabric structures with extensions for 3D solid element and non-linear behavior," *Thin-Walled Structures*, vol. 49, no. 11, pp. 1468–1474, 2011.
- 150** H. K. Dang and M. A. Meguid, "Evaluating the performance of an explicit dynamic relaxation technique in analyzing non-linear geotechnical engineering problems," *Computers and Geotechnics*, vol. 37, no. 1-2, pp. 125–131, 2010.
- 151** D. M. L. da Silva, B. P. Jacob and M. V. Rodrigues, "Implicit and explicit implementation of the dynamic relaxation method for the definition of initial equilibrium configurations of flexible lines," in *25th International Conference on Offshore Mechanics and Arctic Engineering*, Hamburg, Germany, 2006.
- 152** M. Rezaiee-Pajand, S. R. Sarafrazi and H. Rezaiee, "Efficiency of dynamic relaxation methods in nonlinear analysis of truss and frame structures," *Computers and Structures*, vol. 112-113, pp. 295–310, 2012.
- 153** B. H. V. Topping and P. Iványi, "Computer aided design of cable-membrane structures," 2007.
- 154** M. Miki, S. Adriaenssens, T. Igarashi and K. Kawaguchi, "The geodesic dynamic relaxation method for problems of equilibrium with equality constraint conditions," *International Journal for Numerical Methods in Engineering*, vol. 99, no. 9, pp. 682–710, 2014.
- 155** G. Noh and K.-j. Bathe, "An explicit time integration scheme for the analysis of wave propagations," *Computers and Structures*, vol. 129, pp. 178–193, 2013.

- 
- 156** Y. Duan, D. Li and P. F. Pai, “Geometrically exact physics-based modeling and computer animation of highly flexible 1D mechanical systems,” *Graphical Models*, vol. 75, no. 2, pp. 56–68, 2013.
- 157** B. Fierz, “Stabilizing explicit dynamic finite element simulations,” MSc thesis, ETH Zürich, 2013.
- 158** E. Hairer, C. Lubich and G. Wanner, “Geometric numerical integration: Structure-preserving algorithms for ordinary differential equations,” 2nd ed. Springer Berlin Heidelberg New York, 2006.
- 159** P. Cundall, “Explicit-finite difference methods in geomechanics,” in *2nd International Conference on Numerical Methods in Geomechanics*, vol. 1, Blacksburg, USA, 1976, pp. 132–150.
- 160** W. J. Lewis, “Tension structures: Form and behaviour.” Thomas Telford, 2003.
- 161** R. Borghi, “Simple pendulum dynamics: revisiting the Fourier-based approach to the solution,” *ArXiv e-prints*, pp. 1–16, 2013.
- 162** A. Beléndez, C. Pascual, D. Méndez, T. Beléndez and C. Neipp, “Exact solution for the nonlinear pendulum,” *Revista Brasileira de Ensino de Física*, vol. 29, no. 4, pp. 645–648, 2007.
- 163** J. Bishop, “C# 3.0 Design Patterns,” 1st ed. O’Reilly Media, 2007.
- 164** R. Clune, J. J. Connor, J. Ochsendorf and D. Kelliher, “An object-oriented architecture for extensible structural design software,” *Computers and Structures*, vol. 100-101, pp. 1–17, 2012.
- 165** B. Watson, “Writing High-Performance .NET Code.” 2014.
- 166** L. N. Trefethen, “Computing numerically with functions instead of numbers,” *Mathematics in Computer Science*, vol. 1, no. 1, pp. 9–19, 2007.
- 167** S. Chevillard, M. Joldes and C. Lauter, “Sollya: an environment for the development of numerical codes,” in *3rd International Congress on Mathematical Software*, ser. Lecture Notes in Computer Science, vol. 6327, Kobe, Japan, 2010, pp. 28–31.
- 168** R. Green, “Faster Math Functions,” in *Proceedings of Game Developers Conference*, 2003.
- 169** B. H. V. Topping and A. I. Khan, “Parallel computation schemes for dynamic relaxation,” *Engineering Computations*, vol. 11, no. 6, pp. 513–548, 1994.
- 170** V. Rek and I. Němec, “Parallel computing procedure for dynamic relaxation method on GPU using NVIDIA’s CUDA,” *Applied Mechanics and Materials*, vol. 821, no. 1, pp. 331–337, 2016.
- 171** A. Liew, T. Van Mele and P. Block, “Vectorised graphics processing unit accelerated dynamic relaxation for bar and beam elements,” *Structures*, vol. 8, pp. 111–120, Nov. 2016.
- 172** V. Charpentier, P. Hannequart, S. Adriaenssens, O. Baverel, E. Viglino and S. Eisenman, “Kinematic amplification strategies in plants and engineering,” *Smart Materials and Structures*, vol. 26, no. 6, p. 63002, 2017.
- 173** J. E. Marsden, T. Ratiu and R. Abraham, “Manifolds, tensor analysis, and applications,” 3rd ed. Springer Verlag, 2002.



# PUBLICATIONS FROM THE AUTHOR

- 2017** P. Cuvilliers, C. Douthe, L. du Peloux and R. Le Roy, “Hybrid structural skin: prototype of a GFRP elastic gridshell braced by a fibre-reinforced concrete envelope,” *Journal of the International Association for Shell and Spatial Structures*, vol. 58, no. 1, pp. 65–78, 2017.
- B. Lefevre, F. Tayeb, L. du Peloux and J.-F. Caron, “A 4-degree-of-freedom Kirchhoff beam model for the modeling of bending–torsion couplings in active-bending structures,” *International Journal of Space Structures*, vol. 32, no. 2, pp. 69–83, 2017.
- 2016** L. du Peloux, F. Tayeb, O. Baverel and J.-F. Caron, “Construction of a large composite gridshell structure: a lightweight structure made with pultruded glass fibre reinforced polymer tubes,” *Structural Engineering International*, vol. 26, no. 2, pp. 160–167, 2016.
- 2015** L. du Peloux, F. Tayeb, B. Lefevre, O. Baverel and J.-F. Caron, “Formulation of a 4-DoF torsion/bending element for the formfinding of elastic gridshells,” in *Proceedings of the IASS Annual Symposium*, Amsterdam, Netherlands, 2015.
- F. Tayeb, B. Lefevre, O. Baverel, J.-F. Caron and L. du Peloux, “Design and realisation of composite gridshell structures,” *Journal of the International Association for Shell and Spatial Structures*, vol. 56, no. 1, pp. 49–59, 2015.

- 2013** L. du Peloux, F. Tayeb, O. Baverel and J.-F. Caron, “Faith can also move composite gridshells,” in *Proceedings of the IASS Annual Symposium*, Worclaw, Poland, 2013, pp. 1–7.
- F. Tayeb, J.-F. Caron, O. Baverel and L. du Peloux, “Stability and robustness of a 300m<sup>2</sup> composite gridshell structure,” *Construction and Building Materials*, vol. 49, pp. 926–938, 2013.
- 2012** O. Baverel, J.-F. Caron, F. Tayeb and L. du Peloux, “Gridshells in composite materials: construction of a 300m<sup>2</sup> forum for the Solidays’ festival in Paris,” *Structural Engineering International*, vol. 22, no. 3, pp. 408–414, 2012.
- 2011** L. du Peloux, O. Baverel, J.-F. Caron and F. Tayeb, “From shape to shell: a design tool to materialize freeform shapes using gridshell structures,” in *Design Modeling Symposium*, Berlin, Deutschland, 2011.







# Modeling of bending-torsion couplings in active-bending structures

## APPLICATION TO THE DESIGN OF ELASTIC GRIDSHELLS

An *elastic gridshell* is a freeform structure, generally doubly curved, but formed out through the reversible deformation of a regular and initially flat structural grid. Building curved shapes that may seem to offer the best of both worlds: shell structures are amongst the most performant mechanically speaking while planar and orthogonal constructions are much more efficient and economic to produce than curved ones. This ability to “form a form” efficiently is of peculiar importance in the current context where morphology is a predominant component of modern architecture, and envelopes appear to be the neuralgic point for building performances.

The concept was invented by Frei Otto, a German architect and structural engineer who devoted

recently emerged. They go beyond the limitations of conventional materials such as timber and offer at all levels much better technical performances for this kind of application. Finally, it should be noted that the regulatory framework has also deeply changed, bringing a certain rigidity to the penetration of innovations in the building industry. Therefore, the design of gridshells arises in new terms for current architects and engineers and comes up against the inadequacy of existing tools and methods.

In a first part, we deliver a thorough review of this topic and we present in detail one of our main achievements, the ephemeral cathedral of Créteil, built in 2013 and still in service. In a second part, we develop an original discrete beam element with

***In this thesis, which marks an important step in a personal research adventure initiated in 2010, we try to embrace the issue of the design of elastic gridshells in all its complexity, addressing both theoretical, technical and constructive aspects.***

many years of research to gridshells. In 1975 he designed the Multihalle of Mannheim, a 7500 m<sup>2</sup> wooden shell which demonstrated the feasibility of this technology and made it famous to a wide audience. However, despite their potential, very few projects of this kind were built after this major realization. And for good reason, the resources committed at that time cannot guarantee the replicability of this experiment for more standard projects, especially on the economic level. Moreover, the techniques and methods developed by Otto's team in the 1960s have mostly fall into disuse or are based on disciplines that have considerably evolved. New materials, such as composite materials, have

a minimal number of degrees of freedom adapted to the modeling of bending and torsion inside gridshell members with anisotropic cross-section. Enriched with a ghost node, it allows to model more accurately physical phenomena that occur at connections or at supports. Its numerical implementation is presented and validated through several test cases. Although this element has been developed specifically for the study of elastic gridshells, it can advantageously be used in any type of problem where the need for an interactive computation with elastic rods taking into account flexion-torsion couplings is required.

PhD